HIGH TEMPERATURE RESERVOIR CONDENSATE PUMP



DATA SHEET


The HYP-HT2 is a mini reservoir pump with a tank capacity of 4 litres and pumping heads of 7 metres. Complete with high-level alarm contacts, overload protection and CE certified.

230V 40W 2 YEAR GUARANTEE

- Suitable for up to 90°C hot water
- Built-in check valve
- Dual float control design

PHOENIX CONDENSATE PUMPS

Dimensions



Specification

Input Voltage:	230V 50Hz +/-10%
Pumping Head:	7 metres
Max Flow Rate:	675ltr/hr
Tank Capacity:	4ltr
Noise Level:	38dBA
Ambient Temperature:	0-90°C
Power Consumption:	40W

Version 1. 11/2019

HYDRON

HYDRON PUMPS
Unit 3, Drake Business Park
Drake House Crescent, Sheffield, S20 7HT

T: 01246 432325
F: 01246 432324
E: sales@hydronpumps.co.uk

DATA SHEET

Additional Information

- Easy to assemble and clean
- High-level alarm contacts
- High-level alarm contacts

Flow Rates

HORIZONTAL RUN	PERFORMANCE			
	0m	2m	4m	6m
HYP-HT2				
1m	675ltr/hr	625ltr/hr	510ltr/hr	450ltr/hr
2m	500ltr/hr	540ltr/hr	400ltr/hr	350ltr/hr
4m	400ltr/hr	430ltr/hr	320ltr/hr	150ltr/hr
6m	320ltr/hr	340ltr/hr	260ltr/hr	-

Code	Pumping Head	Dimensions (L x W x D mm)
HYP-HT2	7 metres	256 x 136 x 250

HYDRON

HYDRON PUMPS
Unit 3, Drake Business Park
Drake House Crescent, Sheffield, S20 7HT

T: 01246 432325
F: 01246 432324
E: sales@hydronpumps.co.uk