
Interconnecting Services - v9b


Friax GCH air-cooled condensing unit models

SPC-HEVPL2 Vintage


SPC-30/48/82 HEVPL2 VINTAGE — COOLING, HEATING & HUMIDIFICATION



SPC-122 HEVPL2 VINTAGE — COOLING, HEATING & HUMIDIFICATION



SPC-170/230 HEVPL2 VINTAGE — COOLING, HEATING & HUMIDIFICATION



REFRIGERANT CHARGE R513A						
SPC-GCH	**30**	**48**	**82**	**122**	**170**	**230**
Refrigerant charge up to 6m (grams)	500	600	900	950	1650	2450
Additional charge per metre (grams)	20	20	20	20	20	20
Max. pipe run incl. max. 8m riser	20m	20m	20m	20m	20m	20m

NOTES

* Pipe sizes shown are applicable for pipe runs up to 20m (maximum 8m vertical). Good refrigeration practice should be applied regarding oil traps etc. For longer pipe runs contact Heronhill.

Δ Water connection requires a KLPWSECU-XJ Water Connection Kit. A 15mm mains water supply should be provided locally to the indoor unit position. The final connection is made with ¼" micro-bore pipe included in the kit.

Heronhill Air Conditioning Ltd. +44 1823 665660 info@heronhill.co.uk www.heronhill.co.uk

HEVPL2-VTX interconnecting v9b - November 2026
Data taken from Friax installation manuals:
EN-NT-SPC-EVPL-VTX-0626 & EN-NT-SPC-GCH-0526